

FLOGISTIX



FLO-150K

SYNTHETIC LUBRICANT

Part #: 015-001-025

DO NOT MIX WITH OTHER LUBRICANTS

A Product of:
FLOGISTIX, LP
2308 Alcock
Pampa, TX 79065
partsales@flogistix.com
405-536-0000



MADE IN THE USA

MAXIMIZE YOUR RESOURCES



FLOGISTIX

Flogistix FLO-150K Oil

Flogistix FLO-150K is a polyglycol-based lubricant formulated for use in vapor recovery rotary screw gas compressors. The resistance to thinning out by hydrocarbon dilution allows **FLO-150K** to maintain the proper operating viscosity, extending drain intervals and parts life. **FLO-150K** is formulated with rust and corrosion inhibitors, oxidation control agents, and hydrogen sulfide inhibitors to provide additional protection.

FLO-150K lubricant is incompatible with petroleum oils, care should be taken to make sure the two are not mixed.

Additives

Corrosion Protection
H₂S Inhibitors
Viscosity Index Improvers
Pour Point Depressants
Anti- Foam
Gas Release
Anti-Oxidants

	FLO-150K
ISO Viscosity Grade	150
Viscosity	
@ 40°C, cSt	152
@ 100°C, cSt	27.9
Viscosity Index	200
Density	
@ 60°F, g/mL	1.05
Pour Point, °F (°C)	-33 (-36)
Flash Point, °F (°C)	465 (240)
Fire Point, °F (°C)	555 (291)

FLO-150K Oil

- Water Soluble PAG
- Application: Vapor Recovery Rotary Screw
- Resistance to thinning out by hydrocarbon dilution
- Formulated with rust and corrosion inhibitors, oxidation control agents, and hydrogen sulfide inhibitors
- Extended drain intervals, maintain viscosity

MAXIMIZE YOUR RESOURCES